

Axon G2210



migrate from PSTN to wireless EFTPOS



DIAL-UP EFTPOS & ATM

KEY FEATURES

Migrate existing fixed line EFTPOS and ATM terminals to inexpensive wireless GPRS.

Remove monthly line rental charges associated with dial-up pin pads.

Manage and monitor your point of sale network.

Enjoy faster transaction speeds.

Move point of sale equipment anywhere in the store.



Axon G2210

Braintree's Axon G2210 is an EFT to IP converter that allows merchants to convert from a dial-up EFTPOS system to IP over GPRS (general packet radio service).

Being wireless-enabled provides numerous benefits including removing monthly line rental charges and the flexibility to move transaction terminals anywhere around the store. All you need is mains power. Access to telephone sockets no longer dictates where terminals have to be located.

And because it's always on, call set-up and transaction times are fast. This means less waiting in line for customers.

The Axon G2210 includes remote management and monitoring features, which allow simple deployment of new networks, remote configurations, installations and software upgrades, statistics, reporting, connection testing and much more.

The Axon G2210 works on all Australian GSM/GPRS networks (Telstra, Optus and Vodafone), which means excellent coverage - equivalent to the GSM mobile phone network.

What makes the Axon G2210 unique is Braintree's protocol conversion technology, which enables customers on older EFTPOS systems to connect their existing transaction equipment to a GPRS network with no infrastructure changes. Just unplug the transaction terminal from the phone socket in the wall and plug it into the Axon.

It is that easy to wireless-enable your existing dial-up transaction equipment, and all in less than 40 seconds.



TECHNICAL SPECIFICATIONS

| |
|---|
| CONNECTIVITY |
| GSM dual band, GPRS, GSM CSD, GSM HSCSD, Ethernet/IP, Ethernet/PPPoE, |
| PORTS |
| RJ45 Ethernet, RJ45 PSTN Input |
| EFTPOS PROTOCOLS / PROTOCOLS |
| HDLC, TPDU, CLNP, NIST, VISA II, ABP, V21, V22, V22bis, FastConnect / Standard, UDP, TCP, ICMP, TFTP, SNMPv2 / MIB2, DHCP |
| SECURITY |
| IPSec, PPTP, AES, 3DES |
| STANDARDS |
| AS2805, APACS, ISO 8583 |
| DIMENSIONS / WEIGHT |
| 258mm x 173mm x 52mm 958 grams |
| ENVIRONMENT |
| 5-50 degrees C operating temperature 5%-95% relative humidity, non condensing |
| POWER |
| 12V plug pack |
| ACCESSORIES |
| External antenna (thru glass / hole mount), external antenna cable (20m), 12V car plug pack with filter. |

Braintree Communications Pty Ltd

6 Cordelia Street (PO Box 3691)
SOUTH BRISBANE QLD 4101
Australia

Ph: +61 7 3033 8800 Fax: +61 3255 1885

Email: sales@braintree.com.au

www.braintree.com.au